



## **SetDebitCardPin API GATEWAY DOC**

Ujjivan Small Finance Bank Limited  
Grape Garden, No.27, 3<sup>rd</sup> A Cross, 18th Main, 6<sup>th</sup> Block, Koramangala, Bengaluru – 560 095  
This document is for Internal Use Only and may not be reproduced in any form without  
consent of company

## Table of Contents

<b>1. INTRODUCTION</b> .....	3
<b>2. API CONNECT COMPONENTS</b> .....	3
<b>3. TO ACCESS &amp; SUBSCRIBE IN PORTAL</b> .....	3
<b>4. API AUTHENTICATION</b> .....	3
<b>5. SetDebitCardPin API Details</b> .....	3
<b>6. SAMPLE PAYLOAD</b> .....	7

## 1. INTRODUCTION

### 1.1 Design Document Purpose

The purpose of this document is to provide a detailed specification of the **SetDebitCardPin** in sufficient depth to:

- Enable the component to be built and tested.
- Ensure that it can be enhanced, supported and maintained by other areas of the organization after initial implementation.

### 1.2 Design Reviews

The service design will be reviewed within Middleware team and security testing team as needed. Once finalized, design resource will provide an overview to other teams such as front-end application development team and various project resources.

## 2. API CONNECT COMPONENTS

- API Connect is used to expose the service to front end applications.
- Within API Connect, there are multiple Products. The **SetDebitCardPin** API is exposed within **SetDebitCardPin Product**.
- Service Consumers must subscribe to the API. A unique application Identification (client-id) and a secret will be generated.
- The assigned Client-id must be supplied in the header for each API.
- URLs for invoking the services can be found in API Connect Developer portal and mentioned in the below section.

## 3. TO ACCESS & SUBSCRIBE IN PORTAL

Refer Subscription User manual shared during initial on board.

## 4. API AUTHENTICATION

JWT Access token to be passed in JSON wrapper as string value in "JWTTokenValue" field. The Token can be generated by subscribing to **TOKEN API**.

### 4.1 TOKEN API

- **Overview:** To retrieve access token.
- **METHOD:** GET
- **Mandatory HTTP Headers:**
  - X-IBM-Client-Id: xxxxxxxxxxxxxxxxx
  - X-IBM-Client-Secret: xxxxxxxxxxxxxxxxx
- **UAT URL:** <https://apiuat.ujjivansfb.in/ujjivan/development/v1/tokens>

## 5. SetDebitCardPin API Details

- **Overview:**

Service is designed to Set or change debit card PIN by providing mandatory input parameters. The API Gateway makes a backend ESB call which in turn connects to provider system **FSS** of service name **greenPIN**.

- **METHOD:** POST
- **API URL:**  
 UAT : <https://apiuat.ujjivansfb.in/ujjivan/development/v1/PINGeneration/setDebitCardPIN>  
 PROD : To be done
- **Mandatory HTTP Headers:**
  - X-IBM-Client-Id: xxxxxxxxxxxxxxxx
- **Accept:** application/json
- **Content-type:** application/json
- **REQUEST PAYLOAD:**

At API Gateway the request has to be passed as JSON wrapper. The sample payload is as below,

```
{
  "RequestEncryptedValue": "",
  "TransactionId": "",
  "JWTTokenValue": ""
}
```

The individual fields of the Standard JSON Request Payload are described below-

- **RequestEncryptedValue** : This will contain the encrypted value of original REST-JSON request sample.
- **TransactionId** : External partners need to set a transaction ID to uniquely identify every request, in order to retrieve it from an audit trail at a later date.
- **JWTTokenValue** : This value can be obtained by invoking Bank's token generator service.

(For more details on request encryption Refer UjjivanSFB\_API\_Integration\_TechnicalProcess\_document)

- **Actual REST-JSON Input Parameter:**

Element Name	M/O/C	Data Type	Size	Description	Validation Rules
setDebitCardPINReq/reqHdr		Complex			
reqHdr/consumerContext/applicationId	M	String	3	Application id from which request originated. Example IB, MB,HHD, BRN	
reqHdr/consumerContext/terminalId	O	String		Device/Terminal id from where request originated	
reqHdr/serviceContext/uniqueMsgId	M	String		Unique request message id for each message generated from consumer for tracking purpose.	
reqHdr/serviceContext/reqMsgDateTime	M	DateTime		Request time stamp in the format CCYY-MM-DDThh:mm:ss.sss	

reqHdr/ serviceContext/ serviceName	M	String		ServiceName to be provided.	
reqHdr/ serviceContext/ serviceVersion	O	String		Service version to be provided. It's value is 1.	
reqHdr/ providerContext/ providerId	O/F	String	3	Provide application Id from where data expecting	
reqHdr/ userContext/ appUserID	M	String	20	AppUserId will be provided which is created unique to user. Client need to pass this value each and every request.	
reqHdr/ userContext/ appPassword	M	String	64	AppPassword will be provided which is specific to user. Client need to pass this value each and every request.	
setDebitCardPINReq/ body	M	Complex			
body/ cardNumber	M	String	16	Card Number	
body/ transactionAmount	M	String	12	Transaction Amount	
body/ transDateAndTime	M	String	10	Trans Date And Time	MMddhhmmss
body/ traceAuditNumber	M	String	6	Trace Audit Number	Unique Id
body/ transactionTime	M	String	6	Transaction Time	HHMMSS
body/ transactionDate	M	String	4	Transaction Date	MMDD
body/ expiryDate	M	String	4	Expiry Date	MMDD
body/ captureDate	M	String	4	Capture Date	MMDD
body/ retrievalReferenceNu mber	M	String	12	Retrieval Reference Number	Unique Number for Every Transaction
body/ pinToken	M	String	16	Pin Block	

### ➤ RESPONSE PAYLOAD STRUCTURE

A standard JSON wrapper containing encrypted response will be obtained. The encrypted response is of AES/CBC/256 mode with Initialization vector concatenated at the start of original JSON response.

The sample response structure is as below,

```
{
  "ResponseOfEncryptedValue": "<encrypted value>",
  "TransactionId": "162193467244544"
}
```

Using the static key shared by Ujjivan Bank, decryption of the value in tag ResponseEncryptedValue should be performed with AES/CBC/256/IV

TransactionId: This field will contain the transaction ID which was passed in request.

(For more details on response encryption Refer UjjivanSFB\_API\_Integration\_TechnicalProcess\_document)

➤ **ACTUAL OUTPUT PARAMETERS:**

Response					
setDebitCardPINRes/resHdr	Complex				
resHdr/consumerContext/applicationId	M	String	3	Value will be echoed from request message	
resHdr/serviceContext/uniqueMsgId	M	String		Value will be echoed from request message	
resHdr/serviceContext/reqMsgDateTime	O	DateTime		Value will be echoed from request message	
resHdr/serviceContext/serviceName	M	String		Value will be echoed from request message	
reqHdr/serviceContext/serviceVersion	O	String		Value will be echoed from request message	
resHdr/providerContext/providerId	M	String	3	Provider System Id from where data is sending	
resHdr/providerContext/responseMsgDateTime	O	DateTime		Response message date and time stamp.	
resHdr/responseStatus/status	M	String		Response status from ESB	
				Status 0 = Successful, 1 = Failure	
resHdr/responseStatus/esbResDateTime	M	DateTime		Response date time stamp from ESB	
setDebitCardPINRes/body	M	Complex			
body/status	M	Number	2		
setDebitCardPINRes/body/errorInfo	O, Repeating	Complex			Will be populated in case of any business exception from back end
setDebitCardPINRes/body/errorInfo/errorSource	O	String		If Status = 1, value will be populated with error system source	Will be populated in case of exceptions thrown by ESB

setDebitCardPINRes /body/errorInfo/ errorCode	C	String		If Status = 1, value will be populated with error code	
setDebitCardPINRes /body/errorInfo/ errorDescription	C	String		If Status = 1, value will be populated with error description	
setDebitCardPINRes /body/errorInfo/ errorType	O	String	1	If Status = 1, value will be populated with error Type	
resHdr/ additionalDetails/ details1	O/F	String		Future Use	
resHdr/ additionalDetails/ details1	O/F	String		Future Use	
resHdr/ additionalDetails/ details1	O/F	String		Future Use	

### ➤ Error Handling

HTTP Status Code	HTTP Message	More Information
401	Unauthorized	Access token missing or validation
400	Bad Request	The parameters are invalid or missing.
503	Service Unavailable	The parameters were valid but the request failed.

## 6. SAMPLE PAYLOAD



-----END OF DOCUMENT-----