



GetOverDraftAccountDetails API GATEWAY DOC

Ujjivan Small Finance Bank Limited
Grape Garden, No.27, 3rd A Cross, 18th Main, 6th Block, Koramangala, Bengaluru – 560 095

Table of Contents

1. INTRODUCTION	2
2. API CONNECT COMPONENTS	3
3. TO ACCESS & SUBSCRIBE IN PORTAL	3
4. API AUTHENTICATION	3
5. GetOverDraftAccountDetails API Details	3

1. INTRODUCTION

1.1 Design Document Purpose

The purpose of this document is to provide a detailed specification of the **GetOverDraftAccountDetails** in sufficient depth to:

- Enable the component to be built and tested.
- Ensure that it can be enhanced, supported and maintained by other areas of the organization after initial implementation.

1.2 Design Reviews

The service design will be reviewed within Middleware team and security testing team as needed. Once finalized, design resource will provide an overview to other teams such as front-end application development team and various project resources.

2. API CONNECT COMPONENTS

- API Connect is used to expose the service to front end applications.
- Within API Connect, there are multiple Products. The **GetOverDraftAccountDetails** API is exposed within **GetOverDraftAccountDetails Product**.
- Service Consumers must subscribe to the API. A unique application Identification (client-id) and a secret will be generated.
- The assigned Client-id must be supplied in the header for each API.
- URLs for invoking the services can be found in API Connect Developer portal and mentioned in the below section.

3. TO ACCESS & SUBSCRIBE IN PORTAL

Refer Subscription User manual shared during initial on board.

4. API AUTHENTICATION

JWT Access token to be passed in JSON wrapper as string value in "JWTTokenValue" field. The Token can be generated by subscribing to **TOKEN API**.

3.1 TOKEN API

- **Overview:** To retrieve access token.
- **METHOD:** POST
- **Mandatory HTTP Headers:**
 - X-IBM-Client-Id: xxxxxxxxxxxxxxxx
 - X-IBM-Client-Secret: xxxxxxxxxxxxxxxx
- **SIT URL:** <https://apiuat.ujjivansfb.in/ujjivan/development/v1/tokens>

5. GetOverDraftAccountDetails API Details

- **Overview:**

Service is designed to retrieve Over Draft account details. The API Gateway makes a backend ESB call which in turn connects to provider system **CBS** of service name **ODAcctInq**.

➤ **METHOD:** POST

➤ **API URL:**

UAT: <https://apiuat.ujjivansfb.in/ujjivan/development/v1/ODAcctInq/getOverDraftAccountDetails>

PROD : To be done

➤ **Mandatory HTTP Headers:**

■ X-IBM-Client-Id: xxxxxxxxxxxxxxxxx

➤ **Accept:** application/json

➤ **Content-type:** application/json

➤ **REQUEST PAYLOAD:**

At API Gateway the request has to be passed as JSON wrapper. The sample payload is as below,

```
{
  "RequestEncryptedValue": "",
  "TransactionId": "",
  "JWTTokenValue": ""
}
```

The individual fields of the Standard JSON Request Payload are described below-

- **RequestEncryptedValue** : This will contain the encrypted value of original REST-JSON request sample.
- **TransactionId** : External partners need to set a transaction ID to uniquely identify every request, in order to retrieve it from an audit trail at a later date.
- **JWTTokenValue** : This value can be obtained by invoking Bank's token generator service.

(For more details on request encryption Refer UjjivanSFB_API_Integration_TechnicalProcess_document)

➤ **Actual REST-JSON Input Parameter:**

Element Name	M/O/C	Data Type	Size	Description	Validation Rules
getOverDraftAccountDetailsReq / reqHdr		Complex			
reqHdr/consumerContext/applicationId	M	String	3	Application id from which request originated. Example IB, MB,HHD, BRN	
reqHdr/serviceContext/uniqueMsgId	M	String		Unique request message id for each message generated from consumer for tracking purpose.	
reqHdr/serviceContext/reqMsgDateTime	M	DateTime		Request time stamp in the format CCYY-MM-DDThh:mm:ss.sss	
reqHdr/serviceContext/serviceName	M	String		ServiceName to be provided.	
reqHdr/serviceContext/serviceVersion	O	String		Service version to be provided. It's value is 1.	

reqHdr/ providerContext/ providerId	O/F	String	3	Provide application Id from where data expecting	
reqHdr/ userContext/ appUserID	M	String	20	AppUserId will be provided which is created unique to user. Client need to pass this value each and every request.	
reqHdr/ userContext/ appPassword	M	String	64	AppPassword will be provided which is specific to user. Client need to pass this value each and every request.	
getOverDraftAccountD etailsReq/body/	M	Complex		This structure holds to add over draft account details	
body/accountNumber	M	String	16	Account Number to which this account belongs to	

➤ RESPONSE PAYLOAD STRUCTURE

A standard JSON wrapper containing encrypted response will be obtained. The encrypted response is of AES/CBC/256 mode with Initiaization vector concatenated at the start of original JSON response.

The sample response structure is as below,

```
{
  "ResponseOfEncrytpedValue": "<encripted value>",
  "TransactionId": "162193467244544"
}
```

Using the static key shared by Ujjivan Bank, decryption of the value in tag ResponseEncryptedValue should be performed with AES/CBC/256/IV

TransactionId: This field will contain the transaction ID which was passed in request.

(For more details on response encryption Refer UjjivanSFB_API_Integration_TechnicalProcess_document)

➤ ACTUAL OUTPUT PARAMETERS:

Response					
getOverDraftAccount DetailsRes /resHdr	Complex				
resHdr/consumerCon text/applicationId	M	String	3	Value will be echoed from request message	
resHdr/ serviceContext/ uniqueMsgId	M	String		Value will be echoed from request message	
resHdr/ serviceContext/ reqMsgDateTime	O	DateTime		Value will be echoed from request message	
resHdr/ serviceContext/ serviceName	M	String		Value will be echoed from request message	
reqHdr/ serviceContext/ serviceVersion	O	String		Value will be echoed from request message	
resHdr/ providerContext/ providerId	M	String	3	Provider System Id from where data is sending	

resHdr/ providerContext/ responseMsgDateTim e	O	DateTime		Response message date and time stamp.	
resHdr/responseStat us/status	M	String		Response status from ESB	
				Status 0 = Successful, 1 = Failure	
resHdr/responseStat us/ esbResDateTime	M	DateTime		Response date time stamp from ESB	
getOverDraftAccount DetailsRes /body/accountDetails	M	Complex			
accountDetails/accou ntNumber	M	String	16	OverDraftaccount number for which details needs to fetch	
accountDetails / schemeCode	M	String	5	scheme code for the account	
accountDetails /schemeType	M	String	5	scheme type	
accountDetails /acctCurr	M	String	3	Currency code in which account operates	
getOverDraftAccount DetailsRes /body /accountOpenDt	M	Date		Returns the date on which account opened	
getOverDraftAccount DetailsRes /body/ customerDetails	M	Complex			
customerDetails / custId	M	String	50	Customer Id of the realated party	
customerDetails / customerName	M	String	35	Customer Name	
customerDetails / titlePrefix	O	String	5	Title prefix	
getOverDraftAccount DetailsRes /body / accountGeneralInfo	M	Complex			
accountGeneralInfo / eotEnabled	M	String			
accountGeneralInfo / drIntMethodInd	M	String			
accountGeneralInfo / genLedgerSubHeadC ode	M	string	5		
accountGeneralInfo / currency	M	String	3	Currency of the account	
accountGeneralInfo / accountName	M	String	80	Name of the account	
accountGeneralInfo / shortName	M	String	256		
accountGeneralInfo / accountStatementM ode	M	String	1	Default 'P' B - Both N - None P - Passbook S - Statement R - Deposit Receipt	

accountGeneralInfo / cal	M	String			
accountGeneralInfo / type	M	String	12		
accountGeneralInfo / startDt	M	date			
accountGeneralInfo / weekDay	M	Number		If wants to specify on which day in the week SI to be executed	
accountGeneralInfo / holidayStatus	M	String	1	Specify when to execute SI, if the scheduled day is bank holiday. Valid values are S – skip N – NextDay P – Previous day	
accountGeneralInfo / acctStmntNxtPrintDt	M	String			
accountGeneralInfo / dispatchMode	M	String	1	A-Post and email B-Spl. Delivery & Email C-Collect by person D-Courier and E-mail E-E mail only N-No Despatch P-Post Q-Courier S-Special Delivery	
accountGeneralInfo / acctBalCrDrInd	M	String			
accountGeneralInfo / acctBalAmountValue	M	String			
accountGeneralInfo / acctBalcurrency	M	String	3	Currency of the account	
accountGeneralInfo / accrIntCrDrInd	M	String			
accountGeneralInfo / accrIntvalue	M	String			
accountGeneralInfo / accrStartDt	M	date			
accountGeneralInfo / accrWeekDay	M	Number		If wants to specify on which day in the week SI to be executed	
accountGeneralInfo / intRateCode	M	String			
accountGeneralInfo / netIntDrCrInd	M	String			
accountGeneralInfo / netIntvalue	M	String			
accountGeneralInfo / taxCategory	M	String		tax to be collected for the account	
accountGeneralInfo / floorLimitValue	M	String			
accountGeneralInfo / floorLimitCurrency	M	String		Currency of the account	
accountGeneralInfo / withHoldingvalue	M	String			
getOverDraftAccountDetailsRes /body/ relationPartydetails	M	Complex			

relationPartydetails / relPartyType	M	String	100		
relationPartydetails / relPartyTypeDesc	M	String	100		
relationPartydetails / relationPartyCustId	M	String	50	Customer Id of the related party	
relationPartydetails / relationPartyName	M	String	100		
relationPartydetails / relationTitlePrefix	M	String	5	Title Prefix	
relationPartydetails / telephoneNum	M	String	30		
relationPartydetails / address1	M	String	35		
relationPartydetails / address2	M	String	35		
relationPartydetails / address3	M	String	35		
relationPartydetails / city	M	String	35	City code	
relationPartydetails / stateCode	M	String	5	State code	
relationPartydetails / postalCode	M	String	6	Postal Code	
relationPartydetails / countryCode	M	String	6	Country Code	
relationPartydetails / recDelFlg	M	String	1		
getOverDraftAccount DetailsRes /body /baseIValue	M	String	35		
getOverDraftAccount DetailsRes /body/errorInfo	O, Repeatin g	Complex			Will be populated in case of any business exception from back end
getOverDraftAccount DetailsRes /body/errorInfo/ errorSource	O	String		If Status = 1, value will be populated with error system source	Will be populated in case of exceptions thrown by ESB
getOverDraftAccount DetailsRes /body/errorInfo/ errorCode	C	String		If Status = 1, value will be populated with error code	
getOverDraftAccount DetailsRes /body/errorInfo/ errorDescription	C	String		If Status = 1, value will be populated with error description	
disburseLoanRes /body/errorInfo/ errorType	O	String	1	If Status = 1, value will be populated with error Type	
resHdr/ additionalDetails/ details1	O/F	String		Future Use	

➤ Error Handling

HTTP Status Code	HTTP Message	More Information
401	Unauthorized	Access token missing or validation
400	Bad Request	The parameters are invalid or missing.
503	Service Unavailable	The parameters were valid but the request failed.

-----END OF DOCUMENT-----